

<b>EGE UNIVERSITY TEXTILE and APPAREL RESEARCH-APPLICATION CENTER TESTING (PHYSICAL, CHEMICAL, LAUNDRY) LABORATORY</b>	<b>Publish Date</b> : 09.05.2022
	<b>Code</b> : FR.109
	<b>Rev. No / Date</b> : 00 /-
	<b>Page</b> : 1/11
<b>PRICE LIST FORM</b>	

**The Period of Validity: 04 December 2023 - 31 December 2024**

**PHYSICAL ANALYSIS**

<b>ANALYSIS CODE</b>	<b>TYPE OF ANALYSIS</b>	<b>TEST STANDARD</b>	<b>PRICE (TL)</b>
<b>FIBER TESTS and ANALYSIS</b>			
<b>FTM 01</b>	Individual Fiber Length Determination	TS 1140 ASTM D 5103 ISO 6989	1250
<b>FTM 02</b>	<i>Fiber Fineness Measurement</i>		
<b>FTM 02.1</b>	Microscopic Method	TS 1186 ASTM D 2130 ISO 137	1250
<b>FTM 02.2</b>	Gravimetric Method	TS 2874 EN ISO 1973	1250
<b>FTM 03</b>	The number of crimps and percent shortening in the fibers		1000
<b>FTM 04</b>	Amount of Foreign Material	TS 1104 ASTM D 2812	750
<b>FTM 05</b>	Determination of micro dust and foreign material in short stapel fibers (with SDL/Denkendorf micro dust and foreign material analysis instrument MDTA3)		750
<b>YARN TESTS and ANALYSIS</b>			
<b>FTM 06</b>	Fiber Linear Density (Fiber count)	TS 244 EN ISO 2060 ASTM D 1907	750
<b>FTM 07</b>	Elastan (Spandex) Yarn Linear Density (Yarn count)	ASTM D 2951 ASTM D 2653	750
<b>FTM 08</b>	Yarn Breaking Strength and Elongation	TS EN ISO 2062 ASTM D 2256	750
<b>FTM 09</b>	Yarn Twist Count	TS EN ISO 2061 ASTM D 1422 ASTM D 1423	750
<b>FTM 10</b>	Length of Yarn in Bobbins (in meter)		1000
<b>FTM 11</b>	Number of Knots in Yarns		1000
<b>FTM 12</b>	Yarn Evenness -Stapel fiber yarns(USTER TESTER5) -Fancy yarn(USTER TESTER 5)	ISO 16549	1500 1500
<b>FTM 13</b>	Yarn apperance (Contrast Plate)	TS 628	500
<b>FTM 14</b>	Determination of yarn production method (Ring/OE comparison)		1200
<b>FTM 15.1</b>	Yarn-yarn friction (CTT)	ASTM D 3412	1500
<b>FTM 15.2</b>	Yarn-metal friction (CTT)	ASTM D 3108	1500
<b>FTM 16.1</b>	Entanglement properties (CTT)		1500
<b>FTM 16.2</b>	Entanglement stability (CTT)		1500
<b>FTM 17</b>	Yarn hairiness (USTER TESTER 5-CTT)	ASTM D 5647	1500
<b>FTM 18</b>	Stapel fiber/filament determination		500
<b>FTM 19</b>	Filament count -up to 50 pieces -50-150 pieces		500 750

<b>EGE UNIVERSITY TEXTILE and APPAREL RESEARCH-APPLICATION CENTER TESTING (PHYSICAL, CHEMICAL, LAUNDRY) LABORATORY</b>	<b>Publish Date</b> : 09.05.2022
	<b>Code</b> : FR.109
	<b>Rev. No / Date</b> : 00 /-
	<b>Page</b> : 2/11
<b>PRICE LIST FORM</b>	

	-150 and over		1000
<b>FABRIC TESTS and ANALYSIS</b>			
<b>FTM 22</b>	Determination of yarn linear density of yarn removed from the fabric -Warp yarn count -Weft yarn count	TS ISO 7211-5 ISO 7211-5 TS EN 14970	750 750
<b>FTM 23</b>	Determination of yarn twist of yarn removed from the fabric -Warp yarn count -Weft yarn count	TS 256 ISO 7211-4	750 750
<b>FTM 24</b>	Shrinkage ratio of the fabric yarns	TS 254 ISO 7211-3 ASTM 3883	500
<b>FTM 25</b>	Yarn per unit length -Warp -Weft	<i>*TS 250 EN 1049-2 (Accredited)</i> ASTM D 3775 ISO 7211-2	750 750
<b>FTM 26</b>	Mass per unit area	<i>*TS 251-Method 6 (Accredited)</i> <i>*TS EN 12127 (Accredited)</i> ASTM D 3776 ISO 3801 TS EN ISO 29073-1 ASTM 6242	750
<b>FTM 27</b>	Fabric width Fabric length	TS EN 1773 ASTM 3774	350 350
<b>FTM 28</b>	Fabric thickness	TS 7128 EN ISO 5084 ASTM D 1777 TS EN ISO 9073-2 ASTM 5729	500
<b>FTM 29</b>	Fabric construction		500
<b>FTM 30</b>	<i>Fabric strength (Tests applied in weft and warp directions are priced individually)</i>		
<b>FTM 30.1</b>	Strip Method -Warp -Weft	<i>*TS EN ISO 13934-1 (Accredited)</i> ASTM D 5035 TS EN ISO 1421 Metot 1 TS EN ISO 29073-3	1000 1000
<b>FTM 30.2</b>	Grap Method -Warp -Weft	<i>* TS EN ISO 13934-2 (Accredited)</i> ASTM D 5034 TS EN ISO 1421 Metot 2	1000 1000
<b>FTM 31</b>	<i>Tear Strength (Tests applied in weft and warp directions are priced individually)</i>		
<b>FTM 31.1</b>	Pendulum Method -Warp -Weft	TS EN ISO 13937-1 ASTM 1424 TS 3241-2 EN ISO 4674-2	1000 1000
<b>FTM 31.2</b>	Single Tear Method -Warp -Weft	TS EN ISO 13937-2 TS EN ISO 13937-3 TS 3241-2 EN ISO 4674-1 Method B	1000 1000
<b>FTM 31.3</b>	Determination of tear force of wing -Warp	TS EN ISO 13937-3	1000 1000

<b>EGE UNIVERSITY TEXTILE and APPAREL RESEARCH-APPLICATION CENTER TESTING (PHYSICAL, CHEMICAL, LAUNDRY) LABORATORY</b>	<b>Publish Date</b> : 09.05.2022
	<b>Code</b> : FR.109
	<b>Rev. No / Date</b> : 00 /-
	<b>Page</b> : 3/11
<b>PRICE LIST FORM</b>	

	-Weft		
<b>FTM 31.4</b>	Double Tear Method -Warp -Weft	TS EN ISO 13937- 4 TS EN ISO 4674-1 Metot A	1000 1000
<b>FTM 32</b>	Puncture resistance		1500
<b>FTM 33</b>	Bursting Strength	TS EN ISO 13938-1 <b>*TS EN ISO 13938-2</b> <b>(Accredited) TS 7126</b>	1000
<b>FTM 34</b>	Abrasion (friction) resistance - Martindale	TS EN ISO 12947-2 TS EN ISO 12947-3 TS EN ISO 12947-4 ASTM D 4966 TS EN 530 First 20000 cycles: Every added 10000 cycles:	1250 500
<b>FTM 35</b>	<i>Pilling Cycles or time which are demanded beside the procedure will be priced.</i>		
<b>FTM 35.1</b>	Martindale –for 2000 cycles	TS EN ISO 12945-2	1000
<b>FTM 35.2</b>	ICI pilling box -Knitting fabric 7000 cycles -Woven fabric 18.000 cycles	TS EN ISO 12945-1	1000 1000
<b>FTM 35.3</b>	Random Tumble Pilling Tester (30 min.) For every additional 30 min.	TS EN ISO 12945-3 ASTM D 3512	1000 500
<b>FTM 36</b>	Air permeability	TS 391 EN ISO 9237 ASTM D 737	750
<b>FTM 37</b>	Seam strength -Warp direction -Weft direction	TS EN ISO 13935-1 TS EN ISO 13935-2	1000 1000
<b>FTM 38</b>	Seam Slippage -Warp direction -Weft direction	TS EN ISO 13936-1 TS EN ISO 13936-2 BS 3320	1000 1000
<b>FTM 39</b>	Seam density		350
<b>FTM 40</b>	Streth properties of fabrics -Knitted fabric -Woven fabric	TS EN ISO 20932-1 TS EN ISO 20932-2 TS EN ISO 20932-3 ASTM D 2594 TS 6071 ASTM D 3107	1000 1000
<b>FTM 41</b>	For socks -Crosswise elasticity -Longitudinal elasticity	TS 401	600 600
<b>FTM 42</b>	Fit test on socks		1000
<b>FTM 43</b>	Loop to ground yarn ratio in towel fabrics	TS 629 TS EN 14697	500
<b>FTM 44.1</b>	Circular bending rigidity of fabrics	ASTM D 4032	500
<b>FTM 44.2</b>	Bending rigidity (Cantilever method)	TS 1409	750
<b>FTM 45</b>	Fabric Drapeness	TS 9693 TS EN ISO 9073-9	1000
<b>FTM 46.1</b>	Water Vapour Permeability (Permetest)	TS EN ISO 11092	2000
<b>FTM 46.2</b>	Water Vapour Permeability (Cup Method)	EN ISO 420 EN ISO 20344 EN ISO 14268	3500

<b>EGE UNIVERSITY TEXTILE and APPAREL RESEARCH-APPLICATION CENTER TESTING (PHYSICAL, CHEMICAL, LAUNDRY) LABORATORY</b>	<b>Publish Date</b> : 09.05.2022
	<b>Code</b> : FR.109
	<b>Rev. No / Date</b> : 00 /-
	<b>Page</b> : 4/11
<b>PRICE LIST FORM</b>	

<b>FTM 47</b>	Water Vapour Permeability (Hot Plate)	TS EN ISO 11092	3500
<b>FTM 48</b>	Thermal Properties Measurement (Alambeta)		2000
<b>FTM 49</b>	Thermal Resistance Measurement (Hotplate)	TS EN ISO 11092	3500
<b>FTM 50.1</b>	3 D MMD		2000
<b>FTM 52</b>	Resistance to Radiant Heat Transfer	TS EN ISO 6942	7500
<b>FTM 53.1</b>	Determination of resistance to damage by flexing: Weft: Warp: For each additional 100.000 cycles in both weft and warp direction	TS EN ISO 7854	5000
		Method B	5000
		(up to 200.000 cycle)	1500
<b>FTM 53.2</b>	Determination of resistance to damage by flexing: Weft: Warp: For each additional 1000 cycles in both weft and warp direction	TS EN ISO 7854	2000
		Method C	2000
		(up to 2000 cycle)	2000
<b>FTM 54</b>	Reflectivity measurement (For every different condition)		2000
<b>FTM 55.1</b>	Electrical resistance	TS EN 1149-1 TS EN 1149-2	2500
<b>FTM 55.2</b>	Electrical resistance	TS EN 1149-3	5000
<b>FTM 56</b>	UV Resistance	EN ISO 4892 TS EN 277	200 TL/saat
<b>FTM 57</b>	Solar Radiation		500
<b>FTM 58</b>	Thermal Radiation		2000
<b>FTM 59.1</b>	Pile height in carpets	TS 7125 ISO 1766	500
<b>FTM 59.2</b>	Carpet thickness measurement	TS 3374 ISO 1765	500
<b>FTM 59.3</b>	Detection of the number of loops in carpets -Crosswise -Longitudinal	TS 5285 ISO 1763	500
			500
<b>FTM 60</b>	Synthetic turf (pile width, pile length, total pile length, pile fineness, total weight, yarn density in lengthwise and transverse direction, width-length)		5000
<b>APPAREL ACCESSORIES TESTS and ANALYSIS</b>			
<b>FTM 61</b>	<i>Zip Tests</i>		
<b>FTM 61.1</b>	Zip push-pull tests	TS EN 16732	1000
<b>FTM 61.2</b>	Holder resistance	TS EN 16732	1000
<b>FTM 61.3</b>	Edge shield top stopper analysis	TS EN 16732	1000
<b>FTM 61.4</b>	Outer resistance under the lateral force	TS EN 16732	1000
<b>FTM 61.5</b>	Bottom stopper resistance	TS EN 16732	1000
<b>FTM 61.6</b>	Lateral strength resistance of the clamp	TS EN 16732	1000
<b>FTM 61.7</b>	Cursor lock resistance	TS EN 16732	1000
<b>FTM 61.8</b>	Chain width	TS EN 16732	1000
<b>FTM 61.9</b>	Deformation resistance of cursor	TS EN 16732	1000
<b>FTM 61.10</b>	Cursor strain resistance	TS EN 16732	1000
<b>FTM 62</b>	Button resistance	ISO 8124 ASTM D 7142-2	1000
<b>FTM 63</b>	Break strength of touch and close fastener	TS 12242	1000
<b>FTM 64</b>	Break strength from eyelet and snap fabric		1000

<b>EGE UNIVERSITY TEXTILE and APPAREL RESEARCH-APPLICATION CENTER TESTING (PHYSICAL, CHEMICAL, LAUNDRY) LABORATORY</b>	<b>Publish Date</b> : 09.05.2022
	<b>Code</b> : FR.109
	<b>Rev. No / Date</b> : 00 /-
	<b>Page</b> : 5/11
<b>PRICE LIST FORM</b>	

OTHER TESTS			
<b>FTM 65</b>	Taking microscobical photo		1000
<b>FTM 66</b>	Breaking strenght of webbing and tape	TS 3248	1000
<b>FTM 67</b>	Compression Strength		1000
<b>FTM 68</b>	Conpressional recovery	ASTM D 3575	1000
<b>FTM 69</b>	Stifness Measurement (Shore A) (Shore D)	TS ISO 48-4	750
<b>FTM 70</b>	Coating adhesion	TS EN ISO 2411	1000
<b>FTM 71</b>	Components of downs	TS EN 12131	8000
<b>FTM 71.1</b>	Determination of down filling force	TS EN 12130	8000
<b>FTM 72</b>	Density of shoe ground	TS ISO 2781	1000
<b>FTM 73</b>	Drying Rate	AATCC 201	2000
<b>FTM 74</b>	Mask breathability	EN 14683	2000
CARDBOARD TESTS AND METHODS			
For all cardboard tests; At least 25 specimens shall be sent from each of the main body, reinforcement piece and separator parts in A-4 dimensions. Samples should not be banded, folded or stapled.			
<b>FTM 75</b>	Number of grooves, Groove height, Groove length	TS 1119	1000
<b>FTM 76</b>	Bursting strength of cardboard	TS 1119	1000
<b>FTM 77</b>	Puncture resistance of cardboard	TS1119	1000
<b>FTM 78</b>	Edge crushing resistance	TS 1119	1000
PROTECTIVE GLOVES TESTS AND METHODS			
<b>FTM 79</b>	Shear strength in protective gloves	TS EN 388	5000
<b>FTM 80</b>	Puncture resistance in protective gloves	TS EN 388	1500
<b>FTM 81</b>	Tear strength in protective gloves	TS EN 388	1500
<b>FTM 82</b>	Abrasion resistance in protective gloves	TS EN 388	1500

<b>EGE UNIVERSITY TEXTILE and APPAREL RESEARCH-APPLICATION CENTER TESTING (PHYSICAL, CHEMICAL, LAUNDRY) LABORATORY</b>	<b>Publish Date</b> : 09.05.2022
	<b>Code</b> : FR.109
	<b>Rev. No / Date</b> : 00 /-
	<b>Page</b> : 6/11
<b>PRICE LIST FORM</b>	

**CHEMICAL ANALYSIS**

<b>ANALYSIS CODE</b>	<b>TYPE OF ANALYSIS</b>		<b>TEST STANDARD</b>	<b>PRICE (TL)</b>
<b>FIBER ANALYSIS</b>				
<b>KTM 01</b>	Moisture Content		TS 248	750
<b>KTM 02</b>	Oil content (Extraction with Ether)		TS ISO 3074	750 1000
<b>KTM 03</b>	Determination of Foreign Materials for Wool		TS 1104	1200 1200
<b>KTM 04</b>	Maturity			750
<b>KTM 05</b>	Determination of Washing Efficiency of Wool		TS 464	2000
<b>KTM 06</b>	Determination of Wool Solubility in Sodium Hydroxide		TS 885	1000
<b>KTM 07</b>	Determination of non-fiber material			1500
<b>FABRIC PERFORMANCE TEST AND ANALYSIS</b>				
<b>KTM 08</b>	Hydrophilic Cotton Analyses		TS 4786 (Physical +Chemical)	4500
<b>KTM 09</b>	Gauze Analyses		TS 6077 (Physical + Chemical)	15000
<b>KTM 10</b>	Textiles Fabrics- Determination of Resistance to Water Penetration-Hydrostatic Pressure Test	0-1000mm water column	800 1200 1600	380
		1000-5000mm water column		500
		5000-...mm water column		650
<b>KTM 11</b>	Water Repellency of Fabrics by the Bundesmann Rain-Shower Test		TS EN 29865	3000
<b>KTM 12</b>	Water Repellency Spray Test		TS EN ISO 4920	700
<b>KTM 13</b>	Oil Repellency Rating of Fabrics		<b>* TS EN ISO 14419 (Accredited)</b>	1200
<b>KTM 14</b>	Wrinkle Recovery		TS EN ISO 2313-1,2313-2	1000
<b>KTM 15</b>	Flammability for Garments and Upholstery Fabrics		C.F.R. 1610, TS EN ISO 6941, TS EN ISO 6940, TS EN ISO 15025	3000
<b>KTM 16</b>	Flammability test (Floors and Carpets)		TS 5193	3000
	Flammability test (Cigarette ignition source in bed)		TS EN 597-1	3000
	Flammability test (Match match ignition source in bed)		TS EN 597-2	3000
<b>KTM 17</b>	Determination of Formaldehyde		ISO 14184-1 ISO 14184-2	1300
<b>KTM 18</b>	Determination of Ash of Textiles		TS 8003	1000
<b>KTM 19</b>	Dimensional Stability to Washing Every Additional Washing		TS EN ISO 6330	750 200
<b>KTM 20</b>	Appearance After Washing Every Additional		TS ISO 7768, TS ISO 7770 After One	750
	Washing			200

<b>EGE UNIVERSITY TEXTILE and APPAREL RESEARCH-APPLICATION CENTER TESTING (PHYSICAL, CHEMICAL, LAUNDRY) LABORATORY</b>	<b>Publish Date</b> : 09.05.2022
	<b>Code</b> : FR.109
	<b>Rev. No / Date</b> : 00 /-
	<b>Page</b> : 7/11
<b>PRICE LIST FORM</b>	

			Washing	
<b>KTM 21</b>	Dimensional Stability to Dry-Cleaning		TS EN ISO 3175-1,3175-2	1000 400
<b>KTM 22</b>	Relaxation Shrinkage		TS 2374	1500
<b>KTM 23</b>	Felting Shrinkage		TS 2374	1500
<b>KTM 24</b>	Visual Method for the Evaluation of Wrinkle Resistance of Fabrics		TS ISO 9867	1200
<b>KTM 25</b>	Hydrophylicity Hydrophylicity of towel fabrics		TS 866, TS 629 TS EN 14697	750 750
<b>KTM 26</b>	Hydrophylicity of nonvowens			750
<b>COLOUR FASTNESS TESTS</b>				
<b>KTM 27</b>	Colour Fastness to Light	when 4th blue scale is equal to 4	TS EN ISO 105-B02 TS EN ISO 105 B06	2500
		when 6th blue scale is equal to 4		3000
		when 7th blue scale is equal to 4		5000
<b>KTM 28</b>	Colour Fastness to Air Conditions	when 4th blue scale is equal to 4	TS 4460 ISO 105-B04	2500
		when 6th blue scale is equal to 4		3000
		when 7th blue scale is equal to 4		5000
<b>KTM 29</b>	Colour Fastness to Light+Perspiration	For single sample	TS EN ISO 105 B 07	3500
<b>KTM 30</b>	Colour Fastness to Perspiration	Acidic	TS 398 ISO 105-E04	600
<b>KTM 31</b>		Alkaline		600
<b>KTM 32</b>	Colour Fastness to Hypochloride		TS 739 EN 20105-N01	600
<b>KTM 33</b>	Colour Fastness to Chlorinated Water		TS ISO 105-E03	600
<b>KTM 34</b>	Colour Fastness to Saliva		DIN 53160	600
<b>KTM 35</b>	Colour Fastness to Dry-Cleaning		TS EN ISO 105 D01	800
<b>KTM 36</b>	Colour Fastness to Rubbing		<i>* TS EN ISO 105 X 12 (Accredited),</i> AATCC 8 TS EN ISO 105 X 16	600
<b>KTM 37</b>	Colour Fastness to Water		TS EN ISO 105 E 01	600
<b>KTM 38</b>	Colour Fastness to Sea Water		TS EN ISO 105 E 02, AATCC 106	600
<b>KTM 39</b>	Colour Fastness to Acid		TS EN ISO 105 E05	600
<b>KTM 40</b>	Colour Fastness to Alkaline		TS EN ISO 105 E06	600
<b>KTM 41</b>	Colour Fastness to Water Drops		TS EN ISO 105 E07	600
<b>KTM 42</b>	Colour Fastness to Peroxide		TS 400 EN ISO 105 N02	750
<b>KTM 43</b>	Colour Fastness to Ironing		TS 472 EN ISO 105 X	600

<b>EGE UNIVERSITY TEXTILE and APPAREL RESEARCH-APPLICATION CENTER TESTING (PHYSICAL, CHEMICAL, LAUNDRY) LABORATORY</b>	<b>Publish Date</b> : 09.05.2022
	<b>Code</b> : FR.109
	<b>Rev. No / Date</b> : 00 /-
	<b>Page</b> : 8/11
<b>PRICE LIST FORM</b>	

		11	
<b>KTM 44</b>	Colour Fastness to Dry-Heat	TS 3515 EN ISO 105 P01	600
<b>KTM 45</b>	Color fastness to washing	TS EN ISO 105-C06-C07-C08-C09-C10	600
<b>KTM 46</b>	Not to give the perspiration stain to outside		600
<b>KTM 47</b>	Fastness to PVC	TS 7585 EN ISO 105 X10	600
<b>KTM 48</b>	Colour fastness to steaming	TS 7189 EN ISO 105-E11	600
<b>CHEMICAL ANALYSIS</b>			
<b>KTM 49</b>	Quantitative Fiber Analyse (for every single fiber)	TS 4739, TS EN ISO 1833-(1-27)	600
	Quantitative Fiber Analyse -Double -Triple -added fiber		1300 2500 600
<b>KTM 50</b>	Specific fiber determination	The price and method vary according to the fiber type.	2000
<b>KTM 51</b>	Determination of polymer material	The price and method vary according to the material type.	2000
<b>KTM 52</b>	Determination of PVC		1000
<b>KTM 53</b>	Knitting Oil Performance Test (for all temperature and all type of fiber)		2000
<b>KTM 54</b>	Qualitative Determination of Sizing Material		1000
<b>KTM 55</b>	Quantitative Determination of Sizing Material	TS 394	1500
<b>KTM 56</b>	Qualitative Determination of Dyestuffs		2500
<b>KTM 57</b>	Qualitative Determination of Finishing Materials		2500
<b>KTM 58</b>	Allergenic and Corcinogenic Dyestuff Analysis	TS EN 16373-2	3000
<b>KTM 59</b>	Antibacterial Activity Test	ASTM E 2149	5000
<b>KTM 60</b>	Colour Differences	Respect to L,a,b measurement values	1000
		assessment from original sample with spectrophotometer	1000 (Her bir renk için) 1000 (Her bir renk için) 1000
		-assesment from original sample by eye	1000 (Her bir renk için)
		Infrared	1500
<b>KTM 61</b>	Whiteness index		1000
	Metamer index		1000
<b>KTM 62</b>	Azo Dyestuff Determination	EN 14362-1, EN 14362-3	3000
<b>KTM 63</b>	pH Determination	TS EN ISO 3071	750
<b>KTM 64</b>	Qualitative Determination of Sulphur		800
<b>KTM 65</b>	Determination of honeydew		750
<b>KTM 66</b>	Determination of Acid		1000
<b>KTM 67</b>	Determination of Alkali		1000
<b>KTM 68</b>	Determination of Solid Materials		1000



<b>EGE UNIVERSITY TEXTILE and APPAREL RESEARCH-APPLICATION CENTER TESTING (PHYSICAL, CHEMICAL, LAUNDRY) LABORATORY</b>	<b>Publish Date</b> : 09.05.2022
	<b>Code</b> : FR.109
	<b>Rev. No / Date</b> : 00 /-
	<b>Page</b> : 9/11
<b>PRICE LIST FORM</b>	

<b>KTM 69</b>	Determination of Peroxide		1000
<b>KTM 70</b>	Quantitative Determination of Every Single Ion in Water		750
<b>KTM 71</b>	Qualitative Determination of Nickel		800
<b>KTM 72</b>	Qualitative Determination of Iron		800
<b>KTM 74</b>	Comment (comments about in which process step and how the problem occurred and how this problem can be prevented and/or solved)	Tests and analyses that have done additionally will be priced as 50% of the original price	3000
<b>KTM 74</b>	FTIR Analyses		2000
<b>KTM 75</b>	Dimension Change by Water Vapour		1000
<b>KTM 76</b>	Spirality Test After Washing		1000
<b>KTM 77</b>	Waiting at high temperatures (Until 100 °C) (1 day)		1200
<b>KTM 78</b>	Waiting at high temperatures (Until 180 °C) (1 day)		1500
<b>KTM 79</b>	Waiting at low temperatures (-35 – 0 °C) (1 day)		2000
<b>KTM 80</b>	Waiting at low temperatures (-70 – 35 °C) (1 day)		2500
<b>KTM 81</b>	DSC Analysis (Melting Temperature, Melting Energy, Melting Peak Point, Crystallization Peak, Glassy Transition Temperature)	TS EN ISO 11357	2000
<b>KTM 82</b>	Determination of Resistance Against Liquid Chemical Substances	TS EN ISO 6530	600 (Any additional chemical : 220)
<b>KTM 83</b>	Color Change Evaluation with Gray Scale		400
<b>KTM 84</b>	Smear Evaluation with Gray Scale		400

**LAUNDRY TESTS**

(The prices of the following research tests are determined in the company interview.)

<b>YL1</b>	Washing Product-Stain Removal Test (15 stain)	A.I.S.E., In-house	
<b>YL2</b>	Washing Product -Color Care (Color Difference Measurement after 10 washing)	A.I.S.E., ISO 105 A05, ASTM D2244	
<b>YL3</b>	Washing Product – Whiteness Index Measurement after 10 washing	A.I.S.E, ASTM E313	
<b>YL4</b>	Washing Product – Yellowness Index Measurement after 10 washing	ASTM E313	
<b>YL5</b>	Washing Product- Softness Test	Panel Test Instrumental, ASTM D 4032	
<b>YL6</b>	Washing Product- Odor Test Perfume Intensity Panel Test Malodor (synthetic or real conditions) Assessment Panel Test	SNV 195651 Panel Test Panel Test	
<b>YL7</b>	Washing Product- Dissolving Test	Scale Evaluation	
<b>YL8</b>	Washing Product- Foaming Test	Scale Evaluation	

<b>EGE UNIVERSITY TEXTILE and APPAREL RESEARCH-APPLICATION CENTER TESTING (PHYSICAL, CHEMICAL, LAUNDRY) LABORATORY</b>	<b>Publish Date</b> : 09.05.2022
	<b>Code</b> : FR.109
	<b>Rev. No / Date</b> : 00 /-
	<b>Page</b> : 10/11
<b>PRICE LIST FORM</b>	

<b>YL9</b>	Washing Product- Hygiene Test (4 Microorganisms)	EN1276	
------------	---	--------	--

**P.S.: \* signed tests are accredited experiments**

### CONTRACT TERMS

1. Test Request Form is filled by the customer. The responsibility of the information given by the customer belongs to him. When a new report is requested as a result of incomplete or incorrect information, the fee for the newly prepared report is additionally charged. The stamped and signed Test Request Forms are recorded and the fee is conveyed to the customer with the "Customer Price Offer Form". After the fee is paid and the receipt is sent to our laboratory, testing begins. This offer is valid for 1 month. After the test fee is paid, the transaction cannot be canceled.
2. Sampling process and definition of sample is done by the customer. The responsibility of whether the sample is taken in accordance with the test conditions, transportation, packaging and preservation during the period until its acceptance in the laboratory belongs to the customer.
3. The technical documents of the sample must be sent by the customer together with the sample.
4. The request of the customer should given the standard method for the test. If not, tests are carried out using the standard/method agreed with the customer.
5. Any discrepancy between the request or offer and the contract is tried to be resolved before laboratory activities begin. In the case of contract amendments made after the laboratory activity has started, the contract is reviewed and the amendments made are notified in writing to all personnel affected by this situation.
6. Where the test method prevents an unequivocal assessment of the measurement uncertainty, an estimate is made of the application of the method based on theoretical principles and practical experience. For a particular method in which measurement uncertainties of results are established and verified, there is no need to evaluate the uncertainty of measurement for each result if it can be shown that the identified critical influences are under control.
7. If the customer requests a declaration of conformity to a specification or standard for the test (such as suitable/not suitable, passed/failed, within tolerance/out of tolerance), it is checked whether the decision rule is explained in the specification or standard. If the decision rule is explained, the decision rule in the standard or specification is applied. If the decision rule is not explained, the decision rule is determined and recorded in the Test Request Form, by reaching an agreement with the customer in line with the recommendations of the laboratory responsible. Before starting the test, the decision rule determined in agreement with the customer is written on the test report and conformity assessment is made.
8. In case the customer or his representative wishes to witness the experiment, the experiment can be conducted under the supervision of the customer by filling out the "Customer and Visitor Privacy Statement Form".
9. Experimental samples are stored for 3 months and destroyed after 3 months. Since the samples of the trials with the report publication date older than 3 months are destroyed, the test cannot be repeated.
10. All information obtained or created during the performance of laboratory activities is considered confidential information. In the disclosure of confidential information, the explanations given in TS EN ISO 17025:2017, Article 4.2 are followed. Except for legal provisions, only top management can disclose confidential information.
11. Test reports and results are sent to the customer specified in the "Company requesting the test" section of the test request form without obtaining approval.
12. Test reports and Test Price List Form accredited tests are indicated with a "\*" sign. Subcontracting services are not used in laboratory accredited testing services.
13. Lack of information in the test request form, missing sample, etc. For samples that cannot be processed due to other reasons, the arrival date is accepted as the completion date. In such cases, samples are kept in the sample acceptance unit for a maximum of 1 week. During this storage period, the statement "Awaiting sample/information" is written on the samples. At the end of the one-week period, if the deficiency is not completed or the sample is not taken back despite the demand, the sample is destroyed.
14. The customer can take back the remaining samples after the test within 3 months by signing the "Test Sample Retrieved Form".
15. Normal service time is 3 days, expedited service time is 1 day. However, if the required tests (eg, light fastness) take a long time or the laboratory has a high workload, the normal service time may be longer. In case of prolongation of the period, verbal information is given to the customer. When the analysis results are requested to be delivered with a fast service, 50% is added to the analysis fees. An additional fee of 100 TL is charged for revised reports.
16. Unless a different agreement has been made between the parties, the fees in the current "Test Price List Form" are accepted as valid. The current price list is available at <http://tekaum.ege.edu.tr> . Prices in the Price List Form don't include VAT. Our laboratory has the right to revise the Price List. The report preparation fee covers the report to be prepared in only one language. A 30% price difference is charged for reports prepared in a second language. When the report is requested to be evaluated using special statistical methods, 10% price difference is charged.
17. In case of a deviation/non-conformity due to any non-compliance, verbal information is given to the customers on the same day to explain the situation.

<b>EGE UNIVERSITY TEXTILE and APPAREL RESEARCH-APPLICATION CENTER TESTING (PHYSICAL, CHEMICAL, LAUNDRY) LABORATORY</b>	<b>Publish Date</b> : 09.05.2022
	<b>Code</b> : FR.109
	<b>Rev. No / Date</b> : 00 /-
	<b>Page</b> : 11/11
<b>PRICE LIST FORM</b>	

18. If there is a defect or error in any test report given by our laboratory, it is corrected and the corrected report is delivered to the customer.